

## B-EX4D2



- Industrial performance at a real 'value' price point
- High reliability, rugged design, high duty cycle
- Best-in-class print speeds - 12ips
- Flat-head for compatibility with competitor estates
- Emulation technology for easy replacement of legacy systems (Z-Mode is installed)
- Printhead - expected lifetime of 50 km
- Green printing - Energy Star certified, carbon offset manufacture
- Network printer management tool - remote network management
- Free software tools

Rating: Not Rated Yet  
[Ask a question about this product](#)

[Toshiba](#)

### Description

**DIRECT THERMAL PERFORMANCE**  
 Ideally suited to direct thermal printing applications, lowering the cost of ownership over the life of the printer, with no reduction in performance or quality.

**FLEXIBLE MACHINE**  
 Flexible and scalable with a multitude of options, to create the printer to suit your environment. Compatible with the B-EX4T2 series.

**EMULATION CAPABILITIES**  
 Flat head technology, left aligned media and emulation capabilities ensure the B-EX4D2 is ideally suited to quick and easy replacement of legacy competitor estates.

**EASY OF MAINTENANCE**  
 Easy service and maintenance, with snap-in printheads (expected lifetime of 50 km) and field upgradeable options, further lowering the cost of ownership.

**PROTECTING THE ENVIRONMENT**  
 Green credentials include the coveted Energy Star programme and a solvent-free ribbon, as well as delivering 'Carbon Zero' printing. All this, combined with the lowest power consumption in the marketplace\*\*\*.

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| Printhead          | Flat-type                                                     |
| Dimensions         | 310(H) x 278(W) x 460(D) mm                                   |
| Weight             | 17 kg                                                         |
| Interface          | USB 2.0, Ethernet                                             |
| Optional Interface | Wireless LAN, parallel, serial, expansion I/O, RTC & USB host |
| Network Tool       | SNMP                                                          |
| <b>PRINTING</b>    |                                                               |
| Method             | Direct thermal                                                |
| Print Width        | 104 mm (4.09")                                                |
| Max. Print Speed   | 12 ips (304 mm/sec)                                           |
| Resolution         | 200 dpi                                                       |
| Font               | Bitmap and outline                                            |
| Barcode            | Includes GS1 DataBar (RSS) compatibles                        |
| <b>MEDIA</b>       |                                                               |
| Paper Width        | 114 mm                                                        |
| Paper Alignment    | Left                                                          |
| Paper Roll         | 200 mm (7.9")                                                 |
| <b>OPTIONS</b>     |                                                               |
| Cutter             | peel off & internal rewinder                                  |