

CL-S631II



CL-S621II with 300dpi Our desktop range is designed to provide simple, low-cost, high quality printing and the best-in-class CL-S631II offers the finest resolution, providing 300 dpi for the reproduction of logos, pictures and EAN-compliant barcodes. The CL-S631II is supplied as standard with Cross-Emulation™ technology with both Zebra® and Datamax® emulations, plus a range of connectivity options including USB, Ethernet and WiFi. • Direct and thermal transfer printing • Robust all-metal mechanism • Easy media loading

Rating: Not Rated Yet

[Ask a question about this product](#)

[Citizen](#)

Description

Key Benefits

- **Paper width:** Variable paper width - 0.5 inches (12.5 mm) – 4.6 inches (118.1 mm)
- **Paper load:** Durable design - Citizen's proven Hi-Lift™ all-metal mechanism
- **Printing Speed:**
 - Fast print out - 4 inches per second (100 mm per second)
- **Media support:** Large media capacity - holds rolls up to 5 inches (127 mm)
- **Ribbon options:** Wide range of ribbon options - Uses up to 360 metres inside and outside wound ribbons
- **Paper thickness:** Paper thickness up to 0.250mm
- **Hi-Open™ case for vertical opening, no increase in footprint and safe closing.**
- **No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.**
- **Low space requirement - integrated power supply enables clean work station**
- **Energy:**
 - Internal power supply for reliability
- **Media sensor:**

- Black mark sensor
- Adjustable media sensor
- Label gap sensor

- **Tear bar:**

- Standard tear-bar for perforated tags

Specifications

Printing Technology

Print Speed (maximum)

Print Width (maximum)

Media Width (min to max)

Media Thickness (min to max)

Media Sensor

Media Length (min to max)

Roll Size (max), Core Size

Case

Mechanism

Control panel

Flash (Non-Volatile Memory)

Drivers and software

Size (W x D x H) and Weight

Warranty

Emulations (Languages)

Ribbon size

Ribbon winding & type

Ribbon system

RAM (standard Memory)

Cutter

Resolution

Main Interface

Optional interfaces

Thermal Transfer + Direct Thermal

- 4 inches per second (100 mm/s)

4 inches (104 mm)

0.5 - 4.6 inches (12.5 - 118 mm)

63.5 to 254 µm

Fully adjustable gap, notch and reflective black mark

0.25 to 64 inches (6.35 to 1625.6 mm)

Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm)

Core size 1 inch (25mm)

Hi-Open™ industrial ABS case with safe close

Hi-Lift™ metal mechanism with wide opening head

4 buttons and 4 LEDs

16 MB total, 4MB available for user

Free-of-charge on CD with printer, including support for various platforms

- 231 x 289 x 270 mm, 4.5 Kg

2 years on printer. 6 months or 50 Kms printhead

- Datamax® DMX
- Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations
- Zebra® ZPL2®
- CBI™ BASIC Interpreter
- Eltron® EPL2®

2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core

Ink side in or out, switch selectable. Wax, Wax/Resin or Resin Type

ARCP™ automatic ribbon tension adjustment

32MB total, 8MB available for user

Guillotine type, Dealer Installable

- 300 dpi

Triple interface USB and serial built-in plus interface card slot for optional card

- Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps
- Ethernet (10/100 BaseT)
- Parallel (IEEE 1284 compliant)