

CL-S700II



High-speed industrial printing Our CL-S700II series is designed for ease of use; the metal mechanism opens vertically to a full 90° to allow for easy ribbon access, while integrated ribbon control and positioning support precision printing on even small or specialist media. The CL-S700II also comes with the option to print in both direct thermal and thermal transfer modes. • Capacity for ribbons up to 450 metres • Optional rewinder (CL-S700RII) and peeler

Rating: Not Rated Yet

[Ask a question about this product](#)

[Citizen](#)

Description

Key Benefits

- **Paper width: Variable paper width - 1 inch (25.4 mm) – 4.6 inches (118.1 mm)**
- **Paper load: Front access for all operations including media and ribbon changing**
- **Printing Speed:**
 - Ultra fast print out - up to 250mm per second (10 inches per second)
- **Media support: Very large media capacity - holds rolls up to 8 inches (200 mm)**
- **Ribbon options: Wide range of ribbon options - Uses up to 450 metres inside and outside wound ribbons**
- **Paper thickness: Paper thickness up to 0.250mm**
- **Display: Backlight LCD control panel for easy configuration**
- **Front Loading Rewinder for easy rewinding of the backing paper when printing in "peel mode" or when printing batches of labels.**
- **Hi-Open™ case for vertical opening, no increase in footprint and safe closing.**
- **No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.**
- **Low space requirement - integrated power supply enables clean work station**
- **Power switch located in recess at front of printer**

- **Energy:**
 - Internal power supply for reliability

- **Media sensor:**
 - Adjustable media sensor
 - Black mark sensor
 - Label gap sensor

- **Tear bar:**
 - Standard tear-bar for perforated tags

Specifications

Printing Technology	Thermal Transfer + Direct Thermal
Print Speed (maximum)	<ul style="list-style-type: none">• 10 inches per second (254 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25 - 118 mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Case	Hi-Open™ metal case with safe, soft-close feature
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 4-line back-lit graphic LCD
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Size (W x D x H) and Weight	<ul style="list-style-type: none">• 255 x 490 x 265 mm, 13.3 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead
Emulations (Languages)	<ul style="list-style-type: none">• Datamax® DMX• Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations• Zebra® ZPL2®• CBI™ BASIC Interpreter• Eltron® EPL2®
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCPT™ automatic ribbon tension adjustment
RAM (standard Memory)	64MB total, 30MB available for user
Resolution	<ul style="list-style-type: none">• 203 dpi
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Optional interfaces	<ul style="list-style-type: none">• Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps• Ethernet (10/100 BaseT)