

CT-E651



Quick and convenient, the 300mm/s, front-exit CT-E651 is perfect for hospitality and retail alike. The front exit for hospitality protects the mechanism from spills and crumbs. In retail, the compact footprint fits perfectly beneath all-in-one retail systems or alongside a cash drawer - after all it is the same height. Add to that, Bluetooth™ and WiFi™ interface options for great connectivity. • Stylish, modern design • High endurance and exceptional reliability • Flexible interface options with USB, Ethernet and Serial as standard with optional WiFi or Bluetooth

Rating: Not Rated Yet

[Ask a question about this product](#)

[Citizen](#)

Description

Key Benefits

- **Paper exit: Front exit, top loading**
- **Paper width: Variable paper width – 58 and 80 mm**
- **Paper load: Quick and easy media changing - drop-in paper loading**
- **Printing Speed:**
 - Ultra fast print out of receipts - up to 300mm per seconds
- **Paper thickness: Paper thickness up to 0.150mm**
- **Mobile-POS ready**
- **Barcode printing**
- **Same height as cash drawers**
- **Cash drawer connection**
- **Case colour: Available in black or white**

Specifications

Printing Technology	Direct Thermal
Print Speed (maximum)	<ul style="list-style-type: none">• 300 mm/sec.
Print Width (maximum)	72 mm
Media Width (min to max)	59 - 80 mm (+/- 0.5 mm)
Media Thickness (min to max)	53 to 85 µm
Media Sensor	Paper end
Roll Size (max), Core Size	83 mm outside diameter
Case	Stylish flat-top case and top loading
Control panel	2 buttons, 5 LEDs
Flash (Non-Volatile Memory)	8MB
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	<ul style="list-style-type: none">• 125 x 170 x 108 mm. 1.26 Kg
Warranty	2 years including head and cutter
Emulations (Languages)	<ul style="list-style-type: none">• ESC/POS™• Code3of9• UPC-A• UPC-E• EAN-13 (JAN-13)• EAN-8(JAN-8),• Codabar, ITF• CODE39• CODE128• CODABAR(NW-7)• PDF 417• QR Code• GS1-Databar• Composit Symb
Barcodes	Thermal receipt paper
	Guillotine type, full and partial
	CDK / DK connector, RJ12, 2 drawer control
	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
	200 Million pulses or 150 Km, 2 million cuts
	<ul style="list-style-type: none">• CE• TUV• UL• C-UL• FCC• VCCI
Media type	4K bytes / 45 bytes
Cutter	15 codepages, 17 country tables
Drawer kick-out	<ul style="list-style-type: none">• 203 dpi
Power supply	USB 2.0 full speed
Reliability	<ul style="list-style-type: none">• Bluetooth with Apple™ MFi compatibility• Premium Wireless LAN• Serial (RS-232C compliant)• Compact Wireless LAN• Ethernet• Ethernet + USB host
EMC and safety standards	-20 to +60°C (10% to 90% RH non condensing)
Input buffer	
Code pages	
Resolution	
Main Interface	
Optional interfaces	
Storage environment	