

CT-E651



Quick and convenient, the 300mm/s, front-exit CT-E651 is perfect for hospitality and retail alike. The front exit for hospitality protects the mechanism from spills and crumbs. In retail, the compact footprint fits perfectly beneath all-in-one retail systems or alongside a cash drawer - after all it is the same height. Add to that, Bluetooth™ and WiFi™ interface options for great connectivity. • Stylish, modern design • High endurance and exceptional reliability • Flexible interface options with USB, Ethernet and Serial as standard with optional WiFi or Bluetooth

Rating: Not Rated Yet

[Ask a question about this product](#)

[Citizen](#)

Description

Key Benefits

- **Paper exit: Front exit, top loading**
- **Paper width: Variable paper width – 58 and 80 mm**
- **Paper load: Quick and easy media changing - drop-in paper loading**
- **Printing Speed:**
 - Ultra fast print out of receipts - up to 300mm per seconds
- **Paper thickness: Paper thickness up to 0.150mm**
- **Mobile-POS ready**
- **Barcode printing**
- **Same height as cash drawers**
- **Cash drawer connection**
- **Case colour: Available in black or white**

Specifications

| | |
|-------------------------------------|---|
| Printing Technology | Direct Thermal |
| Print Speed (maximum) | <ul style="list-style-type: none">• 300 mm/sec. |
| Print Width (maximum) | 72 mm |
| Media Width (min to max) | 59 - 80 mm (+/- 0.5 mm) |
| Media Thickness (min to max) | 53 to 85 µm |
| Media Sensor | Paper end |
| Roll Size (max), Core Size | 83 mm outside diameter |
| Case | Stylish flat-top case and top loading |
| Control panel | 2 buttons, 5 LEDs |
| Flash (Non-Volatile Memory) | 8MB |
| Drivers and software | Free-of-charge from website, including support for various platforms |
| Size (W x D x H) and Weight | <ul style="list-style-type: none">• 125 x 170 x 108 mm. 1.26 Kg |
| Warranty | 2 years including head and cutter |
| Emulations (Languages) | <ul style="list-style-type: none">• ESC/POS™• Code3of9• UPC-A• UPC-E• EAN-13 (JAN-13)• EAN-8(JAN-8),• Codabar, ITF• CODE39• CODE128• CODABAR(NW-7)• PDF 417• QR Code• GS1-Databar• Composit Symb |
| Barcodes | |
| Media type | Thermal receipt paper |
| Cutter | Guillotine type, full and partial |
| Drawer kick-out | CDK / DK connector, RJ12, 2 drawer control |
| Power supply | 100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC |
| Reliability | 200 Million pulses or 150 Km, 2 million cuts |
| EMC and safety standards | <ul style="list-style-type: none">• CE• TUV• UL• C-UL• FCC• VCCI |
| Input buffer | 4K bytes / 45 bytes |
| Code pages | 15 codepages, 17 country tables |
| Resolution | <ul style="list-style-type: none">• 203 dpi |
| Main Interface | USB 2.0 full speed |
| Optional interfaces | <ul style="list-style-type: none">• Bluetooth with Apple™ MFi compatibility• Premium Wireless LAN• Serial (RS-232C compliant)• Compact Wireless LAN• Ethernet• Ethernet + USB host |
| Storage environment | -20 to +60°C (10% to 90% RH non condensing) |