

LI3608



As a member of the Zebra 3600 Ultra-Rugged Series of scanners, the practically indestructible 1D LI3608-ER corded and LI3678-ER cordless scanners are ready for one of the world’s toughest environments — the warehouse. Designed to capture virtually any 1D barcode from as close as 2 in./5.1 cm to as far as 56 ft./17.1 m away, these scanners provide the ultimate in versatility — workers can capture codes in hand as well as on the top of your warehouse racks. And these scanners are loaded with features that deliver truly unstoppable performance, redefining reliability and management simplicity to drive throughput, accuracy and customer service to a new level.

Rating: Not Rated Yet
[Ask a question about this product](#)

[Zebra](#)

Description

In addition to superior scanning performance, an ultra-rugged design and unparalleled manageability, you get more features that make this scanner easier than ever for your workers to use, including an intuitive aiming pattern for ultra-simple scanning at any distance; mix-and-match feedback modes so workers can see, hear or feel successful scans; an extreme temperature rating for freezer use and more. And Zebra's Network Connect for Automation delivers a seamless connection between LI3600-ER scanners and your Industrial Ethernet network without additional third-party equipment, reducing complexity, and eliminating a point of failure.

Physical Characteristics

Dimensions	Corded: 7.3 in. H x 3.0 in. W x 5.2 in. D 18.5 cm H x 7.6 cm W x 13.2 cm D Cordless: 7.3 in. H x 3.0 in. W x 5.6 in. D 18.5 cm H x 7.7 cm W x 14.2 cm D
Weight	Corded: 11.5 oz./327 g Cordless: 15.0 oz./424 g
Input Voltage Range	Host powered: 4.5 VDC min., 12.6 VDC max. External power supply: 11.4 VDC min., 12.6 VDC max.
Operating Current	LI3608-ER (corded): 250 mA (RMS typical)

Standby Current	LI3608-ER (corded): 110 mA (RMS typical)
Color	Industrial Green
Supported Host Interfaces	USB, RS232, Keyboard Wedge Industrial Ethernet: EtherNet/IP, Profinet, Modbus TCP & Std TCP/IP
Battery	PowerPrecision+ 3100 mAh Li-Ion rechargeable battery
User Indicators	Direct decode indicator; LEDs; beeper; vibration

Wireless Connectivity

Bluetooth Radio	Bluetooth Class 1, Version 4.0 (LE), serial port (SPP) and HID profiles
Data Rate	3 Mbit/s (2.1 Mbit/s) for Classic Bluetooth 1 Mbit/s (0.27 Mbit/s) for Low Energy
Radio Range	Direct line of sight in open air: Class 1: Minimum 300 ft. (100.0 m); Class 2: Minimum 30 ft. (10.0 m)

Regulatory

Environmental	RoHS EN 50581: 2012
Electrical Safety	EU Safety: EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + AC 2011 + A2: 2013; International Safety: IEC 60950-1: 2005 + A1: 2009 + A2: 2013 US/Canada Safety: UL 60950-1, second edition, CAN/CSA-C22.2 No. 60950-1-07
Laser/LED Safety	Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice NO. 50, dated June 24, 2007 and IEC/EN 60825-1:2007 and/or IEC/EN 60825-1:2014
EMI/RFI	IT Emissions: EN 55022: 2010/AC: 2011 (Class B); IT Immunity: EN 55024: 2010; Heavy Industrial: EN 61000-6-2: 2005/AC: 2005; Harmonic Current Emissions: EN 61000-3-2: 2006 + A1: 2009 + A2: 2009 (Class B); Voltage Fluctuation and Flicker: EN 61000-3-3: 2013; Medical Electrical Equipment: EN 60601-1-2: 2007/AC: 2010, IEC 60601-1-2: 2007 (Modified); Radio Frequency Devices: 47 CFR Part 15, Subpart B, Class B Digital Apparatus: ICES-003 Issue 5, Class B

Performance Characteristics

Scans per Full Charge	100,000+
Illumination	660 nm LED
Aimer	655 nm laser
Imager Field of View	30.7° (H)
Image Sensor	2,496 pixels
Minimum Print Contrast	25% minimum reflective difference
Skew/Pitch/Roll	Skew: ± 65°

Pitch: $\pm 65^{\circ}$ Roll: $\pm 45^{\circ}$

User Environment

Operating Temp.	Corded: -22° F to 122° F/-30° C to 50° C Cordless: -4° F to 122° F/-20° C to 50° C
Storage Temp.	-40° F to 158° F/-40° C to 70° C
Humidity	5% to 95% non-condensing
Drop Specification	LI36X8: Withstands multiple 10.0 ft/3.0 m drops to concrete at room temperature LI3678: Withstands multiple 8.0 ft/2.4 m drops to concrete at -20° C to 50° C LI3608: Withstands multiple 8.0 ft/2.4 m drops to concrete at -30° C to 50° C
Tumble Specification	7500 3.3 ft./1.0 m tumbles
Sealing	Scanner: IP65 and IP68 per applicable IEC sealing specifications FLB cradle: IP65
ESD	Per EN61000-4-2, ± 25 KV air discharge, ± 10 KV direct discharge, ± 10 KV indirect discharge
Ambient Light Immunity	0 to 10,000 Foot Candles/0 to 107639 Lux (direct sunlight)

Decode Ranges (Typical)³

Symbology/Resolution	Near/Far
Code 39: 7.5 mil	3 to 28 in./7.6 to 71.2 cm
Code 39: 10 mil	2 to 70 in./5.1 to 177.8 cm
Code 128: 15 mil	5 to 85 in./12.7 to 215.9 cm
Code 39: 20 mil	3 to 140 in./7.62 to 355.6 cm
Code 39: 55 mil	6 to 350 in./15.24 to 889.0 cm
Code 39: 100 mil	20 to 680 in./50.8 to 1727.2 cm
Code 39: 100 mil Reflective	30 to 780 in./76.2 to 1981.2 cm