

ZD510 WRISTBAND PRINTING



Wristbands play a critical role in your healthcare facility. Staff and patients count on wristbands to provide the instant positive identification required to prevent medical errors. You need dependable and fast wristband printing, durable wristbands and consistently scannable barcodes — and with the ZD510-HC, you get it all. The ZD510-HC Wristband Printing solution combines the reliable ZD510-HC direct thermal printer with easy-to-load cartridges containing the only antimicrobial-coated wristbands on the market — Zebra's Z-Band® wristbands. Your IT department will find ZD510-HC printers easy to integrate, manage and secure, thanks to Zebra's Link-OS® operating system and Zebra's powerful Print DNA suite of applications, utilities and developer tools. Increase staff productivity and patient safety with the industry's easiest to use and most dependable wristband printing solution — the ZD510-HC.

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

Standard Features

- Quick and easy wristband cartridge loading
- Automatic print speed setting-up to 4 ips depending on installed cartridge
- Direct thermal printing of barcodes, text and graphics
- Dual-wall frame, impact-resistant plastic
- ZPL® or ZPL II® programming language
- 512 MB Flash memory
- 256 MB SDRAM memory
- Element Energy Equalizer™ (E3™) for superior print quality
- Connectivity: USB Host, USB, Ethernet, Bluetooth Low Energy
- Odometer for print-length tracking
- Illuminated media low/media out indicator
- Tool-less printhead and platen replacement
- Unicode™-compliant for multi-language printing
- Instant media calibration — no wasted media
- Head-up sensor
- XML-enabled printing — allows XML communications from information systems
- ENERGY STAR® qualified
- Link-OS
- Real Time Clock

Dimensions

- 5 in. W x 7 in. H* x 9.5 in. D
127 mm W x 178 mm H* x 242 mm D

- Requires 6 in./153 mm clearance above printer to load cartridge

Printer Specifications

Maximum Print Length: 22 in./558 mm

Minimum Print Length: 3 in./76 mm

Print Widths: 0.75 in./19.05 mm, 1 in./25.4 mm, 1.1875 in./30.16 mm

Resolution : 300 dpi/12 dots per mm

Maximum Print Speed:

Healthcare: 2 in./51 mm per second

Z-Band Fun and Z-Band Splash: 4 in./102 mm per second

Fonts And Graphics

- Character fonts: Standard bitmapped Zebra fonts: A, B, C, D, E (OCR-B), F, G, H (OCR-A), GS, P, Q, R, S, T, U, V & Ø Smooth font (CG Triumvirate™ Bold Condensed)
- Supports user-defined fonts and graphics — including custom logos
- Bitmap fonts are expandable up to 10 times, height- and width-independent. Fonts E and H (OCR-B and OCR-A), however, are not considered in spec when expanded
- Smooth-scalable font Ø (CG Triumvirate Bold Condensed) is expandable dot-by-dot, height-and width-independent, while maintaining edges to a max. 1500 x 1500 dots

Environmental (Printer)

Operating Temperature	40° F to 104° F 4.4° C to 40° C
Storage Temperature	-40° F to 140° F /-40° C to 60° C
Operating Humidity	20%-85% non-condensing R.H.
Storage Humidity	5%-85% non-condensing R.H.

Agency Approvals

Emissions	FCC Part 15, Subpart B, VCCI, RCM
Emissions and Susceptibility	(CE): EN 55032:2012 class B and EN 55024:2010, EN 61000-3-2, EN 61000-3-3, CISPR 32:2015
Safety	CB Scheme IEC 60950-1 and IEC 62368-1, TÜV, NRTL
Power Supply	IEC 60601-1:2012

Fonts And Graphics

- Character fonts: Standard bitmapped Zebra fonts: A, B, C, D, E (OCR-B), F, G, H (OCR-A), GS, P, Q, R, S, T, U, V & Ø Smooth font (CG Triumvirate™ Bold Condensed)
- Supports user-defined fonts and graphics — including custom logos
- Bitmap fonts are expandable up to 10 times, height- and width-independent. Fonts E and H (OCR-B and OCR-A), however, are not considered in spec when expanded
- Smooth-scalable font Ø (CG Triumvirate Bold Condensed) is expandable dot-by-dot, height-and width-independent, while maintaining

edges to a max. 1500 x 1500 dots