

M3 ORANGE+



Fully Rugged Industrial PDA - Cortex-A8 833 MHz - Windows Embedded Handheld 6.5/ Windows Embedded CE 6.0/ Android(comming soon) - 1D / 2D Scanner - 3.2M Pixels Auto Focus Camera - Bluetooth Class II, v2.0 with EDR - WLAN IEEE 802.11 b/g/n - Smart Battery

Rating: Not Rated Yet

[Ask a question about this product](#)

[M3 Mobile](#)

Description

M3 ORANGE+ supports Windows Embedded Handheld 6.5 and Windows Embedded CE 6.0 both of them

Powerful CPU speed with "High-Tier" guarantees faster graphic process and memory access.

M3 ORANGE+ is a slim and light but rugged. It can be used for ticketing and/or asset management wherever the mobile device is needed.

M3 ORANGE+ can be operated within -20 degree to 60 degree and its storage temperature is -30 degree to 80 degree . It will guarantee the normal function at any temperature of working environment.

High resolution and auto focused functionality capture clear images of product and/or documentation.

Termial Emulation: Wavelink, Softogo, Naurtech

Mobile Management: SAP, Wavelink, Soti

Physical Characteristics

DIMENSION (W x H x D)	Millimeters	78.6 x 166.2 x 24.9 78.6 x 165.5 x 40.2 (with HF) 78.6 x 165.5 x 39.8 (27.5) (with UHF)
	Inch	3.0 x 6.5 x 0.9 3.0 x 6.5 x 1.5 (with HF) 3.0 x 6.5 x 1.56 (1.08) (with UHF)
WEIGHT (incl. battery)	Grams	332 362 (with HF) 389 (with UHF)
	Ounce	11.7

DISPLAY	Size	12.7 (with HF) 13.7 (with UHF)
	Type	3.5"
	Pixels	VGA TFT LCD / QVGA (for WinCE)
BATTERY	Type	480 X 640
	Cell	Smart Battery
	Power	Lithium-ion
		3.7 V, 3,300 mA
		3.7 V, 3,600 mA (Optional)

Performance Characteristics

MULTI-PROCESSOR	CPU	Cortex-A8 833 MHz
	Radio	ARM11 series
	OS	Windows Embedded Handheld 6.5
MEMORY	WM	Windows CE 6.0
	CE	
	RAM	256MB
USB INTERFACE	ROM	1GB
	Card Slot	Micro SD, up to 32 GB
	Host	1.1
	Client	2.0

User Environment

TEMPERATURE	Operating	-20 to 60 ° / -4 to 140 °
	Storing	-30 to 70 ° / -22 to 158 °
HUMIDITY		93% non-condensing
Tumble Test		1,000 1.6ft./0.5m tumbles (2,000 drops)
Drop Test		1.8 m / 6 ft
IP Rating		IP65

Wireless Radio Options

WWAN	2G Network (GSM/GPRS/EDGE)	850/900/1800/1900 MHz
	2G Network (CDMA 1x/EVDO)	-
	3G Network (HSDPA/HSPA+)	800/850/AWS/1900/2100 MHz
WAN	Standard	IEEE 802.11
	Bandwidth	b/g/n
	Security	WEP, WPA, WPA2, TKIP, AES, EAP-FAST, EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP- TLS, PEAP-MSCHAPv2, LEAP, CCXv4
BLUETOOTH	Class	Class II
	Version	2.0(WM) 2.1(CE)
RFID	Frequency	HF: 13.56 MHz UHF: 868 ~ 956 MHz
	Standard	HF: ISO 14443 A/B, ISO 15693, ISO 18000-3, I-CODE UHF: EPC C1 G2
GPS		AGPS

General Options

SCANNER	1D	O
	2D	O

CAMERA	Long range Pixels Focus	3.2 M Auto Focus
Keypad	Alpha-Numeric QWERTY AZERTY	31 key 50 key

* The contents of this specification were made based on the "current state" of the product, and this specification may change without notice.